

DHI-IVSS7024DR

4U 24HDDs Intelligent Video Surveillance Server



- Industry embedded micro-controller
- Max 768Mbps incoming bandwidth
- 256-channel IP video access
- Supports RAID 0/1/5/6/10/50/60
- 3 HDMI/1 VGA video output
- Redundant power

System Overview

Dahua IVSS goes beyond the ordinary NVR products. It is an Intelligent Video Surveillance Server that combines video management features with traditional video storage functions in one device. Besides the basic functions as a network video recorder, IVSS is integrated with features such as face detection and face recognition for different business and industrial applications.

An all new UI design supports device operation and maintenance management, improving the value and experience of surveillance view, and serving the era of security big data.

Functions

Face Recognition (with AI camera)

Supports real-time Face Detection & Recognition (with AI camera). Shows real-time face detection and recognition results from AI camera. Records faces with video metadata. Facial features are filtered during real-time display, so as to show only faces with target features. Facial features include gender, age, expression, and more. The linkage actions for face detection and recognition events are configurable, including alarm, buzzer, snapshot, video recording, and more.

AI IVS (with AI camera)

With deep learning algorithm, AI IVS technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, parking detection, loitering detection and crowd gathering estimation) are largely reduced.

Video Metadata (with AI camera)

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Currently, there are four main kinds of metadata in the security industry: Human face, human body, and motor vehicle, non-motor vehicle metadata.

ANPR

Automatic Number Plate Recognition available for convenient entrance/exit management. This feature provides number plate recognition (working with Dahua ITC camera), number plate comparison with blocklist/allowlist, vehicle database management, and vehicle record search.

N+M Hot Standby

The highly reliable redundancy N+M Hot Standby design provides a secure failover technique to ensure immediate backup. In the event of a system failure, the sub device instantly takes over the main device to ensure no data loss.

Fisheye Dewarp

Supports multiple fisheye dewarp modes to make viewing video easy whether it is live or during playback.

Smart Tracking

The automatic tracking PTZ feature automatically tracks a moving target throughout the camera's field of view. This function is ideal for following an object as it moves through airports, parking lots, city centers, or other scenes.

Technical Specification		Resolution	24MP/16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/CIF/QCIF
System		Decoding Capability	2-channel 24MP/3-channel 16MP/6-channel12MP (20fps)/7-channel12MP (15fps)/6-channel8MP (30fps)/12-channel8MP (15fps)/7-channel6MP(30fps)/9-channel5MP(30fps)/11-channel5MP (25fps)/12-channel4MP (30fps)/18-channel4MP (20fps)/19-channel3MP (25fps)/12-channel1080P (60fps)/24-channel1080P (30fps)/36-channel720P (30fps)
Main Processor	Industry embedded micro-controller	Video Output	1-channel VGA output, 3-channel HDMI output, VGA 1/HDMI 1 outputs the same video source. Supports 4K output
Operating System	Embedded Linux OS	Multi-screen Display	Customized display. Max. 36-channel local live view. Max.16-channel PCAPP live view
Operation Interface	WEB (PCAPP), local GUI	Third-party Support	Onvif, RTSP, Sony, Panasonic, Axis, Arecont, Pelco, Canon, Samsung
AI Applications		Operating System	Embedded Linux OS
AI by Camera	Face detection, face recognition, video metadata, IVS (tripwire, intrusion, abandoned object, missing object, fast moving, parking detection, crowd gathering, loitering, parking, and fence-crossing), people counting, smoking detection, call detection	Operation Interface	WEB (PCAPP), local GUI
IVS		Compression	
Perimeter Function (AI by Camera)	256-channel	Video Compression	Smart H.265+/Smart H.264+/H.265/H.264
Human Face Detection		Audio Compression	G.711A/G.711U/PCM/G726
Human Face Properties	Supports 6 properties: Gender, age range (6-level), glasses, expression (8 types), mouth mask, and beard	Network	
Face Detection Performance (AI by Camera) (Channel Number)	128-channel	Protocol	HTTP, HTTPS, TCP/IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P
Human Face Recognition		Mobile Phone	DMSS
Human Face Recognition Performance (AI by Camera) (Channel Number)	128-channel	Interoperability	ONVIF (Profile S, T and G), CGI, SDK
ANPR		Browser	Chrome, PCAPP, IE9 or higher, Firefox
Plate Database Capacity	50 plate databases with 300,000 plate numbers in total Supports allowlist and blocklist	Network Mode	NIC binding mode such as multiple-address mode, load balance, fault-tolerance, etc
Plate Detection Performance	64-channel	Record Playback	
Video Metadata		Multiple-channel Playback	Max. 16-channel playback
Human Body Properties	Gender, age, sleeves length, top color, bottom type, bottom color, bag, rain coat, umbrella, hat, hairstyle, direction, hold a baby, mouth mask	Record Search	Search video detection/manual record/IO alarm/intelligent event/all record file
Vehicle Properties	Vehicle type, vehicle color, plate color, logo, calling, seatbelt, ornament, region	Storage Medium	Internal HDD, SAS disk array enclosure
Non-motor Vehicle Properties	Non-motor vehicle type, non-motor vehicle color, number of passengers, umbrella, rain coat, bag, sleeve length, top color, hat, hair style, mouth mask	Backup Method	HDD, peripheral USB storage device
Metadata Performance (AI by Device) (1080P) (Channel Number)	N/A	Playback Function	1. Play/pause/stop/fast forward/fast backward/reverse play/frame by frame play. 2. Full-screen, backup (clip/file), snapshot, digital zoom, audio on/off
Metadata Performance (AI by Camera) (Channel Number)	64-channel	Storage	
Video Parameters		HDD Group	24
Remote Connection	256	RAID	RAID0/1/5/6/10/50/60
Network Bandwidth	RAID Incoming bandwidth: 768Mbps Recording bandwidth: 768Mbps Outgoing bandwidth: 768Mbps Single HDD Incoming bandwidth: 768Mbps Recording bandwidth: 512Mbps Outgoing bandwidth: 768Mbps	Storage Pool	N/A
Alarm		General Alarm	Motion detect, tampering, local alarm
		Anomaly Alarm	IPC offline alarm, storage error, HDD full, IP conflict, MAC conflict, login lock, fan malfunction
		Intelligent Alarm	Human face detection, human face recognition, video metadata (person/vehicle/non-motor vehicle), IVS, plate recognition, people counting, smoking, call

Alarm Linkage	Record, picture storage (full image), local external alarm output, IPC external alarm output, access & control, audio prompt, buzzer, log, preset, email
Peripheral Interface	
Audio Input	1-channel(reserved)
Audio Output	1-channel, speaker output, audio linkage output
Alarm Input	16-channel
Alarm Output	8-channel
Internal HDD	24 slots, SATA3.0/SAS. Max.16T/HDD
eSATA	1 port
SAS	2 SAS3.0 ports
RS-232	1 port, for debug or transparent COM data
RS-485	1 port, control peripheral PTZ and so on. Supports various protocols
USB	4 ports. 2 USB2.0 port at the front panel and 2 USB3.0 port a the rear panel
HDMI	3 ports; support 4K output
VGA	1 port
Network	4 RJ-45 10/100/1000Mbps self-adaptive Ethernet ports
Power	2 ports
PoE	N/A
General Parameters	
Power Supply	AC100-127V/AC200-240V 50/60Hz
Power Consumption	120W (without HDD, idling) 408W (all HDDs connected)
Net Weight	17 kg (37.48 lb)
Gross Weight	18 kg (39.68 lb)
Dimensions	Chassis: 446 mm × 543.4 mm × 175 mm (17.56 " × 21.39 " × 6.89 ") Max. size: 482.6 mm (with hanger) × 543.4 mm × 175 mm (with feet mat) (19.00 " × 21.39 " × 6.89 ")
Packaging Dimensions	689 mm × 779 mm × 552 mm (27.13 " × 30.67 " × 21.73 ")
Operating Temperature	0 °C to +45 °C (+32 °F to +113 °F)/10%RH–90% RH
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)/30%RH–85% RH
Operating Humidity	10%–90%
Storage Humidity	30%–85%
Operating Altitude	5000 m (16404.20 ft)
Installation Mode	Desktop/rack
Certifications	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 FCC: Part 15 Subpart B UL 60950-1

Dimensions(mm[inch])

